





Madoka





Hello Madoka.

The beauty of simplicity

Japanese for circle, Madoka embodies gentleness and peace. Madoka echoes the distinct blue circle and simplicity of design, which is the very reason why its sleek and elegant look has won such praise, including the Red Dot Product Design Award and iF Design Award.

Madoka guarantees your comfort in the most intuitive way imaginable, featuring just three buttons and a large-figure display.







Available in three attractive colours, Madoka adds style and class to any interior space.

Measuring just 85 x 85 mm, Madoka is extremely compact and will become a fluid part of any background.

White RAL 9003 (glossy)



Silver RAL 9006 (metallic)



Black RAL 9005 (matt)



Sleek design



Madoka combines refinement and simplicity.


The intuitive touch button control enlarges the display and makes Madoka both easy and enjoyable to use.

Much like the perfection that the Japanese name evokes, Madoka gives you perfect control over your individual climate.









User-friendly interface





Madoka Assistant











Simplifies the advanced settings such as schedule or set point limitation

- Visual interface simplifies advanced settings such as schedule setting, energy saving activation, setting restrictions, etc.
- Easy and guick commissioning, saves time and cost for installers
- Featuring Bluetooth® low energy technology

Easy setting of schedules



Advanced user settings



Installer settings



Field settings



Hotel








Intuitive climate control in hotel rooms

Using the simple display, hotel guests can easily set their comfort to their preference.

Optional key card connection and set point restriction guard against misuse and energy wastage, so you can keep costs down.



"Outside home, the office is where we spend most of our time. That's where climate control also comes into play."



Ahead of the curve

For offices the Madoka Assistant offers a simple answer to changing office layouts, by enabling fast and easy system configuration and schedule setting through your smartphone.

Cost-effective infrastructure cooling solution


Madoka also offers a cost-effective solution for server rooms as it comes with standard integrated functions such as duty rotation and back-up operation.

Back-up operation

If one unit fails the other one will automatically take over.

Duty rotation

After a certain period of time, the operating unit will go into standby and the standby unit will take over, extending the system lifetime.







Add class to even the most stylish rooms

Madoka is like a design element of your interior, blending in stylishly and unobtrusively.

It makes scheduling simple, enables you to track your energy usage and activate extra energy saving functions.

All this can be done by smartphone from the comfort of your sofa, within Bluetooth® range of Madoka.





Features

- > Sleek and elegant design
- > Inuitive touch-button contro
- > Two display options: standard and detailed
- Direct access to basic functions (on/off, set point, mode, target values fan speed, louvres, filter icon & reset (4), error & code)
- Three colours to match any interior
- > Compact, measures only 85 x 85 mm
- > Advanced settings and commissioning via smartphone

Hotel application features

- A significant energy saving can be achieved by using the key card and/or window contact integration and a set point restriction. (through the BRP7A* option)
- > Ensures the room cannot heat up above or cool down below a set temperature in order to maintain a minimum level of comfort.

A cost-effective solution for cooling data centres and servers

- > Only in combination with RZAG*/RZQG*
- > Duty rotation: After a certain period of time, the operating unit will go into standby and the standby unit will take over, extending the system lifetime. Rotation interval can be set for 6, 12, 24, 72 or 96 hours, as well as weekly.
- > Back-up operation: If one unit fails, the other unit will start automatically.



Set up all advanced settings on your smartphone



A range of energy-saving functions that can be selected individually

- > Temperature range restriction
- > Setback function
- Adjustable presence detector and floor sensor (available on the Round Flow and Fully Flat Cassettes)
- > Automatic temperature reset (4)
- > Auto off timer

Temperature range restriction means no excessive heating/cooling

 Save on energy by setting the low-temperature limit in cooling mode and the high-temperature limit in heating mode. (1)

Kilowatt-hour consumption tracking (2)

> The kWh indicator displays indicative power consumption for the last day/month/year. (4)

Other functions

- > Up to three independent schedules can be programmed, allowing you to switch easily between them throughout the year (e.g. summer/winter/mid-season) (4)
- > Menu settings can be individually locked or restricted (4)
- > The outdoor unit (3) can be set to guiet mode (4)
- > Real-time clock that updates automatically for daylight saving

⁽²⁾ For Sky Air FBA, FCAG and FCAHG pair combinations only

⁽³⁾ Only available on RZAG*, RZASG*, RZQG*, RZQSG*

⁽⁴⁾ Feature will become available with future app updates from the second half of 2018 onwards.

Technical specifications







Casing	Colour			W = White (RAL 9003 (glossy)) S = Silver (RAL 9006 (metallic)) K = Black (RAL 9005 (matt))
	LED operation Colour		Blue status indicator	
Dimensions	Unit	Height x Width x Depth	mm	85 x 85 x 25
Weight	Unit kg		kg	0.110
LCD	Back light Colour			White
Maximum number of connectable indoor units				1 group (up to 16 indoor units)
Wiring connections	For connection with indoor			P1-P2 wired connection from indoor unit
	Size		mm²	0.75 ~ 1.25
Ambient temperature	Operation		Min.~Max.	-10 ~ 50 °C
	Relative humidity			< 95%
	Storage		Min.~Max.	- 20 ~ 70 °C
Back-up for power failure				Yes - clock stays synchronised for up to 48 hours.
Bluetooth® wireless technology	Protocol			Bluetooth® low energy 4.2 or higher
App for advanced settings				Madoka Assistant
App operation system				Apple iOS 8.0 or higher, Android 5.0 or higher

Daikin Europe N.V.

Naamloze Vennootschap Zandvoordestraat 300 · 8400 Ostend · Belgium www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. Alakin Europe N.V. Has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

Printed on non-chlorinated paper.

Prepared by La Movida, Belgium.

ECPEN18-306

0000 - 06/18

